

9. PERROT

PRODUCT CODE	DESCRIPTION	EXCL VAT	INCL VAT
--------------	-------------	----------	----------

HYDRA



43104HYDRAS	PERROT HYDRA-S FULL CIRCLE GEAR DRIVE POP-UP (OLD)	1 664.00	1 913.60
43104HYDRASPC	PERROT HYDRA-S PART CIRCLE GEAR DRIVE POP-UP (OLD)	1 609.00	1 850.35
43104HYDRA2SVAC	PERROT HYDRA-2-S VIH FULL CIRCLE GEAR DRIVE POPUP	5 030.00	5 784.50
43104HYD2SVACPC	PERROT HYDRA-2-S VIH PART CIRCLE GEAR DRIVE POPUP	4 395.20	5 054.48
43104HYDRA2MVAC	PERROT HYDRA-2-M VIH FULL CIRCLE GEAR DRIVE POPUP	5 180.00	5 957.00
43104HYD2MVACPC	PERROT HYDRA-2-M VIH PART CIRCLE GEAR DRIVE POPUP	4 495.90	5 170.29

VP3



3104VP3	PERROT VP3 VIH PART CIRCLE PISTON DRIVEN POP UP	30 700.00	35 305.00
3103VP3NOZ24	PERROT VP3 24MM NOZZLE	187.80	215.97
3114VP3LID	PERROT VP3 LID WITH CLIP	443.00	509.45
3114VP3VINSERT	PERROT VP3 VALVE INSERT	1 446.70	1 663.71
3114VPNOZKEY	PERROT VP3 ASSEMBLY KEY FOR NOZZLE	485.90	558.79

ZM RANGE

43144ZM22FC	PERROT ZM-22 FULL CIRCLE SPRINKLER	1 720.00	1 978.00
43144ZM22PC	PERROT ZM22W PART CIRCLE SPRINKLER	2 230.00	2 564.50

ZM 22



Application areas

Fruit-growing horticulture, agriculture, over-tree irrigation

Technical specifications

Casting range: 23,2 - 34,5 m
Nozzle variations: 10,0 - 16,0 mm
Op pressure: 3,0 - 7,0 bar
Flow rate: 6,16 - 24,10 m³/h
Trajectory: 22°
Inlet: 1 1/2" male thread

ZN RANGE

43144ZN23PC	PERROT ZN23W PART CIRCLE CANON	11 400.00	13 110.00
-------------	--------------------------------	-----------	-----------

ZN 23 W




Application areas

Waste water irrigation, dust suppression, agriculture

Technical specifications

Casting range: 30,5 - 50,5 m
Nozzle variations: 14,0 - 24,0 mm
2nd nozzle: 6,0 + 7,0 + 8,0 mm
Op pressure: 3,0 - 7,0 bar
Flow rate: 12,08 - 60,22 m³/h
Trajectory: 23°
Inlet: 2 1/2" female thread

43144ZN45W	PERROT ZN45W PART CIRCLE BIG GUN	11 400.00	13 110.00
------------	----------------------------------	-----------	-----------



ZN 45 W

Application areas
stock piles
dust suppression

Technical specifications

Inlet: 2 1/2" female thread
Casting range: 27,5 - 47,0 m
Nozzle variations: 14,0 - 24,0 mm
2nd nozzle: 6,0 + 7,0 + 8,0 mm
Op pressure: 3,0 - 7,0 bar
Flow rate: 12,08 - 54,22 m³/h
Trajectory: 45°

PRODUCT CODE	DESCRIPTION	EXCL VAT	INCL VAT
P2 RANGE			

43144P2S	PERROT P2S 65MM LARGE AREA PART CIRCLE SPRINKLER	10 400.00	11 960.00
----------	--	-----------	-----------



SPECIFICATIONS
Applications: Sports fields, agriculture and dust suppression

Technical Data:
Nozzle Sizes: 16, 20 and 24 mm
Secondary Nozzle: 5 mm
Operating Pressure: 400 - 800 kPa
Radius Range: 35 - 55 m

Flow Rate: 336 - 1011 L/Min
Trajectory: 25°
Inlet: 2 1/2" BSP Female

P2S Performance Data

Operating Pressure	Nozzle 16 mm		Nozzle 20 mm		Nozzle 24 mm	
	L/Min	m	L/Min	m	L/Min	m
400 kPa	336	35.0	506	41.5	715	45.0
500 kPa	375	38.0	566	45.0	800	48.0
600 kPa	411	41.0	620	48.0	876	52.0
700 kPa	444	43.0	670	50.0	946	53.5
800 kPa	475	44.0	716	51.0	1011	55.0

Maximum radius achieved at maximum rotation speed

43144P2M	PERROT P2M 75MM LARGE AREA PART CIRCLE SPRINKLER	15 800.00	18 170.00
----------	--	-----------	-----------



SPECIFICATIONS
Applications: Large turf, agriculture & dust suppression

Technical Data:
Nozzle Sizes: 26, 30 and 34 mm
Operating Pressure: 500 - 800 kPa
Radius Range: 50 - 69 m
Flow Range: 961.7 - 2021.7 L/Min

Rotation Time: 2.3 to 7 minutes
Trajectory: 25°
Inlet: 3" BSP

P2M Performance Data

Operating Pressure	26.0 mm		30.0 mm		34.0 mm	
	L/Min	m	L/Min	m	L/Min	m
500 kPa	961.7	50.0	1258.3	55.0	1598.3	58.0
600 kPa	1053.3	53.0	1378.3	58.0	1750.0	61.0
700 kPa	1136.7	57.0	1488.3	63.0	1890.0	66.0
800 kPa	1215.0	59.0	1591.7	65.0	2021.7	69.0

43144P2MVAR	PERROT P2M-VAR SPRINKLER W/VARIABLE TRAJECTORY	26 600.00	30 590.00
-------------	--	-----------	-----------

ROLLCART

43144RCARTV3	PERROT ROLLCART-V WITH ZE 30 W	28 500.00	32 775.00
--------------	--------------------------------	-----------	-----------

